

PARTNER

CARE, TRUST & RESPONSIBILITY

PT-6910 Series Features

- Options for 2 CPU speeds:
 - *Celeron-M 1.0 GHz, no fan (PT-6910)
 - *Celeron-M 1.5 GHz, with fan (PT-6910-152F) / no fan (PT-6910-152)
- DDR2 Memory
- SATA HDD
- Supports Windows Vista
- No moving parts when configured with Solid State Drive
- Integrated multifunction readers
- Lamp redundant



MSR

Keypad



I-Button



Biometric



PT-6910 Series POS Terminal

www.PartnerTechCorp.com

PT-6910 Series

Evo-lu-tion (n): a process of continuous change from a lower, simpler, or worse to a higher, more complex, or better state. (Merriam-Webster)

Evolution is the cornerstone to the success of a Point of Sale company to meet a demanding retail industry. Partner Tech is proud to introduce the PT-6910 – the next generation of POS terminal crafted from proven, successful innovation. With technology, flexibility, and reliability built into our terminals, the PT-6910 exceeds the standards our customers have come to expect.

Technology – With a higher performance chipset, DDR2 memory, choice of Celeron M 1.0 GHz or 1.5GHz CPU, these improvements guarantee your application will run quickly to meet your high paced environment.

Flexibility – With a 15” adjustable touch display and a long list of modular peripheral options (2x20 CFD integrated rear display, bio-readers/MSR combination, KB-32 keypad and additional 15” rear LCD display) the PT-6910 can be individually matched to your working environment.

Reliability – Using advanced technological design, the PT-6910 offers a fan less design and optional Solid State Drive configuration reducing failure points to allow you to focus on your business and remove downtime.

Partner Tech delivers the systems and solutions you have come to demand from you POS equipment to run your business!



0-60 degrees tilt angle



Dual Display



Spill proof design



Quick release latch design for easy maintenance



Easy to remove HDD under the cover



Air intake filter design to increase airflow and easy maintenance

Item	PT-6910-100	PT-6910-152	PT-6910-152F
CPU Type (L2 Cache)	Intel Celeron-M 1.0GHz, FSB 400MHz, Fanless	Intel Celeron-M 1.5GHz, FSB 400MHz, Fanless	Intel Celeron-M 1.5GHz, FSB 400MHz, W/Fan
LCD	15" Active TFT color LCD, resolution 1024 x 768		
Touch	5-wire Resistive touch (RS-232 interface)		
Memory	1G (up to 2G)		
Ethernet	10/100/1000 Mbps		
Storage	Internal 3.5" type SATA HDD 80GB or USSD		
I/O Interface	<ul style="list-style-type: none"> 6 * COM ports (COM1~4 at back I/O, COM5~6 on M/B) (COM3/4 provides DC +5V/12V with BIOS setting) 1 * DB-15 VGA port 1 * DB-25 for LPT port 1 * RJ11 port for 2 cash drawer(+24V) 1 * PS2 Keyboard port 1 * PS2 Mouse port 1 * RJ-45 LAN port with activity and link LEDs 2 * Audio ports (1 * Line-out , 1 * MIC-in) 6 * USB 2.0 (2 in the front; 2 in the back; 2 on the M/B) 1 * DC +19V yellow power adaptor connector 		
Expansion Options	<ul style="list-style-type: none"> Compact Flash card socket, IDE interface 1 * Mini PCI socket 		
Optional Peripherals	3 track magnetic reader Customer display module (2 x 20 VFD) 802.11 b/g Mini PCI Module support WiFi function Biometric Reader, Smart Card Reader, I-Button, RFID reader KB-32 32-keys keypad 2nd monitor(Dual screen)		
Operation System	Windows XP, XP embedded, CE.Net, Linux (Fedora, Red Hat) , WEPOS, POSReady		
Power Supply	AC100~240V/DC19V, 4.75A, 90 watt power adaptor (3P), 24V-tolerant		
Dimensions	Physical:344(W)x259(D)x331(H)mm		
Operating Temperature	0°C ~ +40°C		
Storage Temperature	-20°C ~ +60°C		
Operating & Storage Humidity	10%~80%		
Certification	CE/FCC Class A, UL, cUL, CB, VCCI, BSMI, CCC		

Partner Tech USA Inc.
 51 Parker
 Irvine, CA 92618
 Tel: (949) 598-1888
 Fax: (949) 598-0088
 www.PartnerTechCorp.com



*Specifications subject to change without notice